



CP- UVR-1601K1-V3

16 Ch. Tribrid 1080P HDCVI DVR



Main Features

- Support HDCVI/Analog/IP Video input
- All channel 1080N/720P Realtime or 1080P non Realtime Recording
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 6TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro



*Product casing and specifications are subject to change without prior notice

CP- UVR-1601K1-V3

16 Ch. Tribrid 1080P HDCVI DVR



Feature

Processor
Operating System
Two-way Talk
User Interface
Video Input
Video Output
Video Standard
Compression

Video Resolution

Video Recording

Video Display Split

Privacy Masking

Audio Input

Audio Output

Motion Detection

Video Loss

Camera Blank

Smart Phone

Hard Disk

Trigger Events

Recording Mode

Search Mode

Playback

Backup Mode

Interface Ports

Record Interval

Max User Account

Specification

Embedded processor

Embedded LINUX

Reuse audio input/output channel 1

GUI

16 channel, BNC

1 HDMI, 1 VGA

Analog: NTSC/PAL, HDCVI: 1080P/720P HDCVI Camera, IP: 16+8 up to 5Mp

H.264 / G.711

1080P(1920×1080)/1080N(960×1080)/720P(1280×720)/960H(960×576/960×480)/D1
(704×576/704×480)/HD1(352×576/352×480) /BCIF(704×288/704×240) CIF
(352×288/352×240) / QCIF(176×144/176×120)

Main Stream: 1080P(1~15fps) 1080N/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps), Extra
Stream: CIF/QCIF(1~15fps)

1/4/8/9/16

4 rectangular zones (each camera)

1 channel, RCA

1 channel, RCA

Supports

Supports

Supports

iPhone, iPad, Android, Windows Phone

1 SATA port, up to 6TB

Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips

Manual, Schedule(Regular(Continuous), MD), Stop

Time/Date, MD & Exact search (accurate to second)

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous
camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom

USB Device/Internal SATA burner/Network

1 HDMI, 1 VGA, 2 USB2.0, 1 RS485

1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

128 users



CP- UVR-1601K1-V3

16 Ch. Tribrid 1080P HDCVI DVR



Feature

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

RJ-45 port (10/100M/1000M)

HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P, ONVIF Version 2.4 conformance

DC12V/2A

10W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

260mm x 220mm x 40mm

0.75Kg(without HDD)



*Product casing and specifications are subject to change without prior notice