

CP- UNC-TB40ZL6-MD**4 MP Full HD IR Bullet Camera - 60Mtr.****Main Features**

- 1/3" 4MP PS CMOS Image Sensor
- Max 20fps@4M and 25/30fps@3M
- H.264 and MJPEG dual-stream encoding
- WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC
- 2.7~12mm motorized lens
- IR Range of 60 Mtrs, IP67, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



CP- UNC-TB40ZL6-MD

4 MP Full HD IR Bullet Camera - 60Mtr.



Feature

Image Sensor

Minimum Illumination

Shutter Speed

White Balance

Gain Control(AGC)

Lens

Back Light Compensation

Video Compression

S/N Ratio

Video Streaming

Resolution

Privacy Mask

ICR

WDR

Protocol

Ethernet

User Account

Smart Phone

IR

Micro SD

Operating Temperature

Power Source

Power Consumption

Weatherproof Standard

Dimension

Weight

Specification

1/3" 4MP Progressive scan CMOS

0. 1Lux/F1.4 (Color), 0Lux/F1.4(IR on)

Auto/Manual, 1/3(4)~1/10000s

Auto/Manual

Auto/Manual

2.7mm~12mm motorized Lens

BLC/ HLC/ WDR(120dB)

H.264/ H.264H/ H.264B/ MJPEG

More than 50dB

Main Stream: 4M(1~20fps)/3M(1~25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)

4M(2688×1520)/4M(2560×1440)/3M(2304×1296)/1080P(1920×1080)/720P(1280×720)/D1
(704×576/704×480)/CIF(352×288/352×240)

Up to 4 areas

Auto(ICR)/Color/B/W

Supports

IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP,
DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS,Bonjour, ONVIF, PSIA, CGI

RJ-45 (10/100Base-T)

20 Users

iPhone, iPad, Android, Windows Phone

IR Range of 60 Mtr.

Micro SD, Max 128GB

-30°C~+60°C , Less than 95%RH

DC12V, PoE (802.3af)

Max 12.5W

IP67

72mm× 80mm× 212.8mm

0.65kg