

**CP- UNC-TB20FL6-MS****2 MP Full HD IP IR Bullet Camera - 60Mtr.****Main Features**

- 1/2.8" 2MP progressive CMOS Image Sensor
- 25/30fps@1080P
- H.264 plus and H.264 dual-stream encoding
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- 2.7~12mm varifocal lens
- IR Range of 60 Mtrs, IP67, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



# CP- UNC-TB20FL6-MS

2 MP Full HD Network IR Bullet Camera - 60Mtr.



## Feature

Image Sensor  
Minimum Illumination  
Shutter Speed  
White Balance  
Gain Control(AGC)  
Lens  
S/N Ratio  
Back Light Compensation  
Video Compression  
Video Streaming  
Resolution  
Privacy Mask  
Protocol  
Ethernet  
User Account  
Smart Phone  
IR  
Micro SD  
Ingress Protection  
Operating Temperature  
Power Source  
Power Consumption  
Dimension  
Weight

## Specification

1/2.8" 2Megapixel progressive scan CMOS  
0.01Lux/F1.4 (Color), 0Lux/F1.4(IR on)  
Auto/Manual, 1/3(4)~1/100000s  
Auto/Manual  
Auto/Manual  
2.7mm~12mm  
More than 50dB  
BLC/ HLC/ DWDR  
H.264+/ H.264  
Main Stream:1080P/960P/720P(1 ~ 25/30fps) , Sub Stream:D1/CIF(1 ~ 25/30fps)  
1080P(1920x1080)/1.3M(1280x960)/720P(1280x720)/D1(704x576/704x480)/CIF  
Up to 4 areas  
IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour  
RJ-45 (10/100Base-T)  
20 Users  
iPhone, iPad, Android, Windows Phone  
IR Range of 60 Mtr.  
Micro SD, Max 128GB  
IP67  
-30°C~+60°C , Less than 95%RH  
DC12V, PoE (802.3af)  
Max 7.5W  
72mm × 80mm × 212.8mm  
0.65kg