

Firmware Release Notes

Product: Encoder Firmware

Version: A1D-310-V4.09.22-NB

Date: 24th June, 2011

Limitation

1. No Variable Frame Rate mode.
2. Motion Detection not available for MJPEG.

Enhancement

1. New function: Bonjour
2. New function: Event handler. This allows configurable rule-based trigger-response sets with a maximum 10 of rules and weekly schedulers
 - 2.1 Available event triggers are:
 - a. Scheduled
 - b. DI
 - c. Motion Detection
 - d. Day/Night mode switch
 - e. Video loss (Video Server only)
 - f. Ready for service. (This will trigger the event responses once the device boots up.)
 - g. Service is not available. (This triggers the event response when the device is shut down via web UI "Save and Reboot.")
 - 2.2 Available event responses are:
 - a. DO
 - b. Upload Video / snapshot to FTP / email / HTTP CGI
 - c. Send Notification message to email / HTTP CGI
 - d. Change Motion Detection Profile
 - e. Send URL commands
 - f. Change to Night profile
 - 2.3 Manual Event: user may select one event rule in Manual Event list, and it can be triggered via Trigger button on web UI
3. New function: Support getting Video stream via URL command
Please use this sample command into the address bar.
http://camera_ip:port/cgi-bin/cmd/system?GET_STREAM
Before using this URL, please make sure that:
 - a. You are using Mozilla Firefox

- b. The device is set to use MJPEG codec
 - c. RTP B2 Header has been disabled. (Uncheck Enable RTP B2 Frame in the RTP setting page.
 - d. Audio In must be disabled.
- 4 New function: Support RTSP/RTP Over HTTP Tunneling protocol
Please disable RTP B2 Header on camera and use the sample command in your multimedia player(e.g.VLC)
RTSP://account:password@camera_ip:rtsp_port/unicast/media1
- 5 New function: IEEE 802.1X port-based Network Access Control

IEEE 802.1X*

Enabled

EAPOL Version V1 V2

User Name

User Password

CA Certificate

User Certificate

User Private Key

* New settings will only take effect after [Save & Reboot]

- 6 Update languages: Dutch, French, German, Japanese, Portuguese, Russian, Simplified Chinese, Spanish, and Traditional Chinese languages updated.

Modified

- 1. None

Remove

- 1. Anonymous login
- 2. IPv6 in web UI since this function is automatically, users do not need to enable or disable the function.
- 3. HTTPS function

Remark

- 1. SD Card reserved for support in future firmware versions and hardware that contain SD card.