

GV-POE0810 8-Port Gigabit 802.3at PoE Switch





- 8-port 10/100/1000BasedTX, PSE/Power over Ethernet
- IEEE 802.3at Compliant (8 Ports at Full 15.4 W)
- Max. 130 W power consumption
- Auto-MDI/MDI-X
- Auto-Negotiation
- Non-Blocking
- 11" Metal Case
- Up to 7 GV-IP Cameras support

Introduction

The GV-POE0810 is an 8-port 10/100/1000BasedTX , PSE Desktop PoE Gigabit Switch. The switch supports IEEE 802.3at Power over Ethernet standard, up to 30 W per port and maximum 130 W power consumption per system, and no special network cable is required for connecting your powered devices (PD), such as IP cameras. The switch is designed for small or medium network environment to strengthen its network connection and efficiency. It also gives you the option of installing it in an 11" cabinet with a rack-mount kit or underneath a desk.

Dimensions





- 1 -GV-POE0810 - May 15, 2014



Specifications

Ports		
Number of Ports		8 ports
		8-port 10/100/1000BaseTX with RJ-45 Connectors, PoE+
Performance		
MAC Address		8 K
Buffer Memory		1.37 M bits
Transmission Method		Store and Forward
Transmission Media		10/100BaseTX Cat. 5 UTP/STP
		1000BaseT Cat. 5e, 6 UTP/STP
Filtering/Forwarding Rates		10 Mbps port - 14,880 pps
		100 Mbps port - 148,800 pps
		1000 Mbps port - 1,488,000 pps
Mechanical Characteristics		
		Per Port: Link/Act
LED Indicators		PoE Act/Status
		Power
Electrical Characteristics		
PoE Power	Input	100 ~ 240 V/AC, 50 ~ 60 Hz
	Output	IEEE 802.3at Compliant Voltage, Per Port Max. 30 watts
		(8 Ports at Full 15.4 W / 4 Ports at Full 30 W)
Max. Power Consumption		130 W
General		
Dimensions (H x W x D)		44 x 266 x 161 mm (1.73" x 10.47" x 6.34")
Weight		1.52 kg (3.35 lb)
Operating Temperature		0°C ~ 40°C (32°F ~ 104°F)
Storage Temperature		-20°C ~ 90°C (-4°F ~ 194°F)
Humidity		10 to 90% RH (non-condensing)
Standards and Regulatory		
		IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.ab 1000BaseT
Standards		IEEE 802.3x Flow Control
		IEEE 802.3at Power Over Ethernet (PoE+)
Regulatory		CE, FCC Class A

Note: Specifications are subject to change without notice.

Front View



Packing List

- 1. GV-POE0810 x 1
- 2. Screw x 8
- 3. Rack Mount Kit x 1
- 4. AC Power Cord x 1
- 5. Software CD x 1
- 6. GV-POE0810 Quick Start Guide x 1

- 2 -