

CP- VNC-B20-MD**2 MP Full HD Box Camera****INDIGO****Main Features**

- 1/2.8" 2MP PS CMOS Image Sensor
- Max 25fps@1080P
- H.264 and MJPEG Triple-stream Encoding
- WDR, Day/Night(ICR), 2D/3D-DNR, AWB, AGC, BLC
- C/CS Mount lens, Micro SD
- 6 KV surge protection designed for network interface
- Mobile Software for Android, iOS
- CMS Software: IVMS



CP- VNC-B20-MD**2 MP Full HD Box Camera****Feature**

Image Sensor
Minimum Illumination
Shutter Speed
White Balance
Lens
Gain Control(AGC)
Video Compression
S/N Ratio
Video Streaming
Resolution
Video Output
Frame Rate
Motion detection
Privacy Mask
ICR
Audio Input
Audio Compression
Audio Output
Alarm IN
Alarm Out
WDR
Interface
Protocol
Ethernet
OSD
Operating Temperature
Humidity
Power Source
Power Consumption
Weatherproof Standard
Dimension
Weight

Specification

1/2.8" 2MP Progressive scan CMOS
Colour: 0.02 Lux (F1.2, 50IRE), Black & White: 0.008 Lux (F1.2, 50IRE)
Auto/Manual, 1/6~1/8000 s
Auto/Manual
C/CS Mount Lens
Auto/Manual
H.264/MJPEG
>52dB
Triple
2MP @ 25fps
1 BNC, impedance 75Ω; amplitude 1 V [p-p]
1080P(1920x1080)/720P(1280x720)/D1720x576) @ 25 fps
Up to 2 areas
Up to 4 areas
IR-cut filter with auto switch (ICR)
impedance 35 kΩ; amplitude 2 V [p-p]
G.711
impedance 600 Ω; amplitude 2 V [p-p]
2 IN
1 Out
Upto 120 dB
1 RS485 (support Pelco-D/P)
IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP,RTP,RTSP,Qos,DNS,DDNS,NTP,FTP,UPnP,HTTP, Onvif
10M/100M Base-TX Ethernet
Up to 8 OSDs
-20°C ~ +60°C (-4°F ~ 140°F)
≤ 90% RH(non-condensing)
24 V AC, 12 V DC, or PoE (IEEE802.3 af)
Power consumption: 4.8 W (6.8W with ICR on)
IP66
151.5 x 71 x 65 mm (6.0" x 2.8" x 2.6") (excluding the lens)
0.48 kg

 **CP- VNC-B20-MD****2 MP Full HD Box Camera****Feature****Specification**