

CP- VNC-T13FR3-M**1.3 MP HD VF IR Array Bullet Camera - 30Mtr.****INDIGO****Main Features**

- 1/3" 1.3MP PS CMOS Image Sensor
- Max 25fps@1.3MP
- H.264 and MJPEG Triple-stream encoding
- DWDR, Day/Night(ICR), 2D/3D-DNR, AWB, AGC, BLC
- 2.8~12mm Varifocal Lens
- IR Range of 30 Mtrs, Micro SD, IP66, PoE
- Mobile Software for Android, iOS
- CMS Software: IVMS



CP- VNC-T13FR3-M

1.3 MP HD VF IR Array Bullet Camera - 30Mtr.



Feature

Image Sensor
Minimum Illumination
Shutter Speed
White Balance
Lens
Gain Control(AGC)
Video Compression
S/N Ratio
Video Streaming
Resolution
Frame Rate
Privacy Mask
ICR
Audio Input
Audio Output
Alarm IN
Alarm Out
WDR
Protocol
Ethernet
OSD
IR
Micro SD
Operating Temperature
Humidity
Power Source
Power Consumption
Weatherproof Standard
Dimension
Weight

Specification

1/3" 1.3MP Progressive scan CMOS
Colour: 0.06 Lux (F1.4, 50IRE), Black & White: 0.03Lux (F1.4, 50IRE)
Auto/Manual, 1/6~1/8000 s
Auto/Manual
2.8~12mm Varifocal Lens
Auto/Manual
H.264/MJPEG
>50dB
Triple
1.3MP @ 25fps
1.3MP(1280x960)/720P(1280x720)/D1720x576) @ 25 fps
Up to 4 areas
IR-cut filter with auto switch (ICR)
impedance 35 k Ω ; amplitude 2 V [p-p]
impedance 600 Ω ; amplitude 2 V [p-p]
1 IN
1 Out
Digital
L2TP,IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP,PPPoE,RTP,RTSP,Qos,NTP,FTP,HTTP,SNMP,SIP,
10M/100M Base-TX Ethernet
Up to 8 OSDs
IR Range of 30 Mtr.
Up to 128 GB
-35°C ~ +60°C (-31°F ~ 140°F)
 \leq 90% RH(non-condensing)
12 V DC, or PoE (IEEE802.3 af)
3.5W (5.5W with IR on)
IP66
253.4 x86 x71.7 mm (9.98" x 3.4" x 2.8")
0.93 kg