






## Comparison Table of GV-IP Decoder Box and GV-IP Decoder Box Plus

|                               |   | GV-IP Decoder Box   | GV-IP Decoder Box Plus   | GV-IP Decoder Box Lite  |
|-------------------------------|---|---|--|---|
|                               |   |  |  |  |
| <b>Video</b>                  |   |   |  |   |
| <b>Video Stream</b>           |   | 64  | 64   | 16  |
| <b>Video Codec</b>            |   | H.264   | H.264  | H.264   |
| <b>Audio Codec</b>            |   | Not supported   | G.711  | G.711   |
| <b>Video Input Resolution</b> | <b>Single View</b>                            | 2560 x 1920   | 2048 x 1944  | 1920 x 1080   |
|                               | <b>Quad View</b>                              | 1280 x 720  | Top-left Grid: 2048 x 1944<br>Other 3 Grids: 1920 x 1080                           | 1920 x 1080   |
|                               | <b>9 View</b>                                 | Not Supported   | 1280 x 720   | Not Supported   |
| <b>Video Output at 60 Hz</b>  | <b>HDMI</b>                                   | 480p, 720p, 1080i, 1080p  | 720p, 1080p  | 720p, 1080p   |
|                               | <b>VGA</b>                                    | 640 x 480, 1024 x 768, 1280 x 768   | 1024 x 768   | 1024 x 768  |
| <b>Network</b>                |   |   |  |   |
| <b>Interface</b>              |   | 10/100 Ethernet   | 10/100/1000 Ethernet   | 10/100/1000 Ethernet  |
| <b>Protocols</b>              |   | ONVIF, PSIA, RTSP, TCP  | ONVIF, RTSP, TCP   | ONVIF, TCP  |
| <b>Wifi Support</b>           |   | Yes   | No   | No  |
| <b>Mechanical</b>             |   |   |  |   |
| <b>Control</b>                |   | IR Remote   | USB Mouse  | USB Mouse   |
| <b>GV-Joystick Supported</b>  |   | GV-Joystick, GV-Joystick V2   | GV-Joystick V2   | GV-Joystick V2  |
| <b>Connectors</b>             | <b>Power Adapter</b>                          | 12 / 3A DC Jack (Max. 36 W)   | 12 / 3A DC Jack (Max. 36 W)  | 12 / 3A DC Jack (Max. 36 W)   |
|                               | <b>Ethernet</b>                               | RJ-45   | RJ-45  | RJ-45   |
|                               | <b>Monitor Output</b>                         | HDMI, VGA   | HDMI, VGA  | HDMI, VGA   |
|                               | <b>USB</b>                                    | USB 2.0   | USB 2.0 x 4  | USB 2.0 x 2   |
|                               | <b>SD Card</b>                                | SD / SDHC Card (Class 6 or above)   |  | Not Supported   |
| <b>General</b>                |   |   |  |   |
| <b>Operating Temperature</b>  | 0°C ~ 40°C (32 °F ~ 104 °F)                   |   |  |   |
| <b>Operating Humidity</b>     | 20 % ~ 80 % (with no condensation)            |   |  |   |
| <b>Dimensions (W x H x D)</b> | 182.3 x 28.9 x 131 mm (7.18" x 1.14" x 5.16") | 162.3 x 34.4 x 107.6 mm (6.39" x 1.35" x 4.24")                                   | 162.3 x 34.4 x 107.6 mm (6.39" x 1.35" x 4.24")                                    |   |
| <b>Weight</b>                 | 615 g   | 555 g   | 528 g  |   |
| <b>Regulatory</b>             | CE, FCC compliant                             | CE, FCC, LVD, RCM compliant   | CE, FCC, LVC compliant   |   |



|                 |         |   |   |
|-----------------|---------|---|---|
| <b>Language</b> | English | English, French, German, Italian,<br>Japanese, Portuguese, Russian,<br>Spanish, Traditional Chinese | English, French, German, Italian,<br>Japanese, Portuguese, Russian,<br>Spanish, Traditional Chinese |
|-----------------|---------|---|---|

**Note:** All specifications are subject to change without notice.